

Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Körapur® 125 RAL 8017 schokobraun

Product code : 00000000015040080

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

stance/Mixture

: Adhesive, Sealant

Recommended restrictions

on use

: For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13

PT-4486-851 Mindelo - Vila do Conde

+351 229 288 200

E-mail address of person

responsible for the SDS

: EU-MSDS@hbfuller.com

1.4 Emergency telephone number

Emergency telephone number : In case of poisoning:

GBK-EMTEL International

Tel.(24h): +49(0)6132/84463 (all languages)

In case of transport accidents:

Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 /

GBK)

National Poisons Information Centre (NPIC): 01 809 2566 (24

hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Körapur® 125 RAL 8017 schokobraun

Version Revision Date: SDS Number: Date of last issue: 13.10.2022 1.1 06.01.2023 100000023080 Date of first issue: 13.10.2022

Hazard pictograms :

Signal word : Danger

Hazard statements : H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary statements : Prevention:

P261 Avoid breathing dust.

P284 Wear respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate

4,4'-Methylenediphenyl diisocyanate, oligomers

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

iessionai us

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		



Version Revision Date: SDS Number: Date of last issue: 13.10.2022
1.1 06.01.2023 100000023080 Date of first issue: 13.10.2022

Reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- 0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Acute Tox. 4; H312	>= 1 - < 10
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47- 0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 ——————————————————————————————————	>= 0,1 - < 1
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6 500-040-3 01-2119457013-49- 0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Respiratory system) Carc. 2; H351 ————————————————————————————————————	>= 0,1 - < 1

Körapur® 125 RAL 8017 schokobraun

Version	Revision Date:	SDS Number:	Date of last issue: 13.10.2022	
1.1	06.01.2023	100000023080	Date of first issue: 13.10.2022	
			Acute inhalation toxicity (dust/mist): 1,5 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Even minimal concentrations of isocyanate can lead to a reac-

tion in sensitised people.

Symptoms that may occur include the following:

irritation of the eyes, nose, throat and lungs, possibly together with a dry throat, a feeling of chest tightness and breathing

difficulties.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the

accident.

Show this safety data sheet to the doctor in attendance.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of unconsciousness bring patient into stable side posi-

tion for transport.

In case of skin contact : Treat affected skin with cotton wool or cellulose.

Wash off with plenty of water. Use a mild soap if available.

If skin irritation persists, call a physician.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical atten-

tion if eye irritation develops or persists.

If swallowed : If accidentally swallowed obtain immediate medical attention.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : In instances of existing sensitisation towards isocyanates, a

doctor should be consulted with regards to work-related contact with other sensitising substances, or substances which

irritate the airway.

Treatment for exposure should be geared towards monitoring

symptoms and the patient's clinical condition.



Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

It must be ensured that the patient has sufficient ventilation

and oxygen supply.

Isocyanates can cause sensitisation of the airways, or asthma-like symptoms (bronchospasms). Delayed breathing

symptoms, including lung oedema, may occur.

People who have shown signs of breathlessness after considerable exposure should remain under observation for 24-48

hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Water spray

Alcohol-resistant foam

Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

May release toxic, irritating and/or corrosive gases. In case of fire, the following substance(s) may occur:

Hydrogen chloride (HCI)

Nitrogen oxides Sulphur oxides (SOx) Carbon monoxide

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

Further information : In the event of fire, wear self-contained breathing apparatus.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation.



Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Send for recovery or disposal in suitable containers. Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Dispose of contaminated material as waste according to sec-

tion 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of dust and aerosols.

Use only with adequate ventilation.

Handle with care.

Keep eye wash bottle available on working place.

Avoid release to the environment.

Keep away from children.

Advice on protection against

fire and explosion

In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing

equipment ready in case of nearby fire. The product contains small quantities of organic solvents. The possibility of an ignitable vapour / air mixture forming is very slight but, under certain local conditions, this should not be overlooked. Keep

away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep dark, cool and dry. Do not freeze.

Further information on stor-

age conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase

pressure and may lead to the container exploding.

Storage class (TRGS 510) : 13, Non Combustible Solids

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

Version Revision Date: SDS Number: Date of last issue: 13.10.2022 1.1 06.01.2023 100000023080 Date of first issue: 13.10.2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Occupational Expo				_ <u>_</u>
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
polyvinyl chloride	9002-86-2	OELV - 8 hrs (TWA) (Respira- ble dust)	1 mg/m3	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m3	IE OEL
di-"isononyl" phthalate	28553-12-0	OELV - 8 hrs (TWA)	5 mg/m3	IE OEL
4,4'- methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min (STEL)	0,07 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min (STEL)	0,07 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	, , , , , , , , , , , , , , , , , , , ,	3	(-,	
Substance name	End Use	Exposure routes	Potential health effects	Value
4,4'- methylenediphenyl diisocyanate	Workers	Dermal	Acute systemic effects	50 mg/kg
	Workers	Inhalation	Acute systemic effects	0,1 mg/m3
	Workers	Dermal	Local effects	28,7 mg/cm2
	Workers	Inhalation	Local effects	0,1 mg/m3
	Workers	Inhalation	Long-term systemic	0,05 mg/m3

Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

		effects	
Workers	Inhalation	Local effects	0,05 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
4,4'-methylenediphenyl diisocya-	Fresh water	> 1 mg/l
nate		
	Marine water	> 0,1 mg/l
	Soil	> 1 mg/kg
	Sewage treatment plant	> 1 mg/l

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber

Remarks : Direct contact with the isocyanate-based product must be

avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the protective glove pro-

ducer and this has to be observed.

Skin and body protection : Protective clothing

When carrying out activities where unintentional skin contact with the isocyanate-based product may occur (e.g. during maintenance work, or when opening a barrel), wear long-

sleeved protective clothing and gloves.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Protective measures : Keep away from food, drink and animal feedingstuffs.

Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling

the product.

Avoid contact with the eyes and skin. Store protective clothing separately.

Environmental exposure controls

Air : Suppress (knock down) gases/vapours/mists with a water

spray jet.

Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid

Colour : brown

Odour : solvent-like

Odour Threshold : is not determined

Melting point/freezing point : is not determined

Boiling point/boiling range : is not determined

Flammability : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

Upper flammability limit

is not determined

Lower explosion limit / Lower

flammability limit

Lower flammability limit

is not determined

Flash point : Not applicable

Auto-ignition temperature : not self-igniting

Decomposition temperature : Not applicable

pH : is not determined

Solubility(ies)

Water solubility : not miscible or difficult to mix, reacts with water

Partition coefficient: n-

octanol/water

no data available

Vapour pressure : is not determined

Density : 1,44 g/cm³ (20 °C)

Relative vapour density : is not determined

9.2 Other information

Explosives : Not explosive

Evaporation rate : is not determined



Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alcohols, amines, aqueous acids and alkalis.

Mixture reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure

and produces a risk of bursting.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

Reaction mass of ethylbenzene and xylene:

Acute dermal toxicity : LD50 (Rat): 1.468 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist



Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

4,4'-Methylenediphenyl diisocyanate, oligomers:

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Product:

Mobility : Medium: Soil

Remarks: Do not allow product to reach ground water, water

bodies or sewage system.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Do not dispose of waste into sewer.

Hand over to disposers of hazardous waste.

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to

the necessary technical regulations.

The generation of waste should be avoided or minimized

wherever possible.

Incinerate under controlled conditions in accordance with all

local and national laws and regulations.

Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

08 04 09* waste adhesives and sealants containing or-

ganic solvents or other dangerous substances

08 04 10 waste adhesives and sealants other than

those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing or-

ganic solvents or other dangerous substances

08 04 12 adhesive and sealant sludges other than

those mentioned in 08 04 11

Waste packaging:



Version 1.1	on Revision Date: 06.01.2023	SDS Number: 100000023080	Date of last issue: 13.10.2022 Date of first issue: 13.10.2022
		15 01 01 15 01 02 15 01 04 15 01 10* nated by dang	paper and cardboard packaging plastic packaging metallic packaging packaging containing residues of or contamigerous substances.
C	Contaminated packaging	: Disposal mus	t be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: 4,4'-methylenediphenyl diisocyanate

(Number on list 74)

4,4'-Methylenediphenyl diisocya-

nate, oligomers

o-(p-isocyanatobenzyl)phenyl isocy-

anate

dibutyltin dilaurate (Number on list

30)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

: Not applicable

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

RoHS: 2011/65/EU, Restriction of Hazardous Substanc-

es

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Not applicable

Not applicable

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous

substances.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 4,17 %, 60,0 g/l

Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

REACH : On the inventory, or in compliance with the inventory

Körapur® 125 RAL 8017 schokobraun

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.10.2022

 1.1
 06.01.2023
 100000023080
 Date of first issue: 13.10.2022

Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

Penetrometer test according to ADR 2.3.4.3 Test result: solid (penetration after 5 s < 15 mm)

Burning test according to 33.2.1.4 "Manual of Tests and Crite-

ria" (Recommendations on the TRANSPORT OF

DANGEROUS GOODS [United Nations]):

Burning rate: ≤ 2.2 mm/s (Not a dangerous good according to

ADR class 4.1)

Contact Point : Prepared by: Global Regulatory Department

EU-MSDS@hbfuller.com

Classification of the mixture: Classification procedure:

Resp. Sens. 1 H334 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN



Version Revision Date: SDS Number: Date of last issue: 13.10.2022 1.1 06.01.2023 100000023080 Date of first issue: 13.10.2022